# X SEAL Data Sheet

Acme Reg. No. 0526080

The Acme **X Seal** is a versatile smooth ribbon pull-tight seal manufactured from Polypropylene material. The design features rolled heat staking technology to secure the metal spring insert to the body, which provides clear evidence of tampering if forced open or cut. The seal can be manufactured with a **Short Tag (ST)** or **Long Tag (LT)** in three different lengths and with a 2mm diameter ribbon making this seal ideal for most applications particularly where there are small sealing apertures.

Technical Data

Recommended Applications

Airline in-flight duty free or Catering Trolleys, Baggage, Refineries, Fuel and Oil Tankers, Chemical Drums, ATM Dispensers, Coin Boxes, Cash Bags, Gaming Machines, Postbags, Fire doors, Lockers

Material

Body - Polypropylene
Insert - Spring Stainless Steel

Available Operating Lengths

(ST) Short Tag (30mm)

(L1) 15cm (overall 18cm)
(L2) 20cm (overall 23cm)
(L3) 30cm (overall 33cm)

(LT) Long Tag (50mm)

(L1) 15cm (overall 20cm)
(L2) 20cm (overall 25cm)
(L3) 30cm (overall 35cm)

Tag Marking Dimensions

Short Tag - 18mm x 20mm
Long Tag - 18mm x 40mm

Ribbon Diameter

2mm

Average Breaking Strength

15kg

Marking

Laser, Foil or Thermo Transfer
Consecutively numbered as standard
Optional Customer name/logo
Optional Laser or Thermo Transfer Barcoding

Colours

Foil: red, blue, green, yellow and orange, black, white.
Laser: pastel shades of pink, blue, green, yellow and peach, also black and white.
Thermo Transfer: all of the above.
Other colours may be available on request.

Packaging

Standard Packaging   : 10 per mat and 1,000 seals/carton

Carton Dimensions **ST & LT** : (L1) - 23cm x 20cm x 22cm
: (L2) - 29cm x 20cm x 22cm
: (L3) - 37cm x 20cm x 22cm

Carton weight **(ST)**   : (L1) - 1.45kg/carton
: (L2) - 1.65kg/carton
: (L3) - 1.95kg/carton

Carton weight **(LT)**   : (L1) - 1.8kg/carton
: (L2) - 2.0kg/carton
: (L3) - 2.3kg/carton

Office Bitola:
+389 (0) 47 203330

Electrolux Macedonia
www.electrolux.mk
electrolux@t-home.mk

Office Skopje:
+389 (0) 2 3298130